



CE 22ZWWC48L-G26CAB-X-40SNSN-110
RoHS DINGS' MOTION
Work order
DATE REV00

REVISION			
REV.	DATE	DESCRIPTION	DRAWN BY




Encoder		
PIN#	Description	Color
1	+5V	Red
2	Gnd	Black
3	A+	White
4	A-	Yellow
5	Z+	Orange
6	Z-	Gray
7	PE	Transpar ent
8	B+	Green
9	B-	Blue

Pole pairs	2
Reduction ratio	26
Gearbox efficiency	80%
Rated voltage	24V
Rated current	1.1A
Rated speed	7800RPM
Rated torque	20mN·m
Rated power	16.3W
Lead screw diameter	$\phi 6$ mm
Lead screw lead	1 mm
Rated line speed	5mm/s
Dielectrical strength	500VAC 1ms,1s
Insulation resistance	100M Ω (500VDC)
Duty type	S2
Protection level	IP40
Insulation class	B130C
Cooling method	IC410
Rated thrust	750N
Stroke	40mm



CUSTOMER

WIRING CHART



EXCITING SEQUENCE

wire gauge	Motor wire	Color	wire gauge	Hall wire	Color
26AWG	U	Brown	26AWG	+5V	Red
	V	Yellow		Hall U	Gray
	W	Green		Hall V	White
				Hall W	Blue
				GND	Black

NOTICE TO PERSONS RECEIVING THIS DRAWING
THIS DRAWING IS ONLY CONDITIONALLY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POSSESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER SHOWN IN THIS DRAWING ARE AND REMAIN, EXCEPT AS MAY BE OTHERWISE INDICATED BY WRITTEN NOTICE HEREON, THE EXCLUSIVE PROPERTY OF SAID CORPORATION. THIS DRAWING MAY BE REPRODUCED ONLY BY LICENSEES AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSED MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSEES AND ASSOCIATE CONTRACTORS.

UNLESS OTHERWISE SPECIFIED ALL
DIMENSIONS ARE IN MILLIMETERS AND
TOLERANCES ARE AS BELOW PER ISO2768-cK.

LINEAR		ANGULAR	
0~3	± 0.2	0~10	$\pm 1.5^\circ$
3~6	± 0.5	10~50	$\pm 1^\circ$
6~30	± 0.8	50~120	$\pm 30'$
30~120	± 1.5	120~400	$\pm 15'$

DRAWN

Kevin

DATE

2025/12/3

APPRVD

DATE

MODEL

22ZWWC48L-G26CAB-X-40SNSN-110

DINGS			
SIZE	A3	SHEET	1 of 1
SCALE	1: 1	REV	00